

## Product parameters

<b>ELECTRICAL SPECIFICATION</b>	
Rated voltage input/output	400V~ (three-phase)
Input Voltage/Output voltage	AC400V~ (L1+L2+L3+N+PE)
Input frequency	50Hz
Max. output power	44kW (three-phase)
Max. output current	32A
<b>WORKING ENVIRONMENT</b>	
Protection degree	IP65
Environment temperature	-25°C~+45°C
Relative humidity	0-95%non-condensing
Maximum altitude	< 2000m
Cooling	Natural air cooling
<b>MOUNTING ACCESSORIES</b>	
Wall-mounting bracket/Ground-mounting pole	Yes/Opt
Product model	<b>GD4702-057</b>
<b>FUNCTION AND ACCESSORY</b>	
Bluetooth	Yes
Ethernet	Yes
4G	Yes
4.3-inch color display	Yes
Swipe Card Reader	Yes
RCD	Type B
LED Indicator light	Yes
Intelligent power adjustment	Yes
Starting mode	The app launched/Swipe the card to start
Fuselage size	450*430*120mm

1. It has card swiping start and remote stop start, and is equipped with rechargeable IC card.
2. Reservation charging function, which can be charged regularly according to user needs, and it will automatically end when fully charged.
3. Equipped with display screen, real-time display of charging information estimation Fill time.
4. With overload protection, overvoltage protection, undervoltage protection, short circuit protection, overtemperature protection, emergency stop and other functions.